

FIG. 1




FIG. 2




FIG. 3




FIG. 4

File Descriptor Block (FDB)




FIG. 5




FIG. 6

CATALOG/FILE/SECTOR
DESCRIPTOR
(CFSD) DMB PORTION

✓702

710	+00	LENGTH OF CFSD		
	+04	CFP #		
	+08			
	+0C			
	+10			
	+14			
	+18			
	+1C			
	+20			
	+24			
	+28			
	+2C			
	+30			
	+34			
	+38			
	+3C	TSD LOCATION FOR FORMATTING		
			706	
			704	

FIG. 7




FIG. 8

SECTOR DESCRIPTOR DATA STREAM
FLOPPY DRIVE

CH	SS	SC	SS	SS	CH	SS	SC	CH	SS
----	----	----	----	----	----	----	----	----	----

FIG. 9




FIG. 10




FIG. 11

SDF SD	~1204
CURRENT SDP	~1206
OEF POINTER BLOCK	~1208
SDP POINTER BLOCK	~1210
CURRENT SPBM #	~1212
# FREE ENTRIES IN CURRENT SPBM	~1214
GC OF CURRENT SPBM	~1216
TOTAL # OF SPBMs FOR DRIVE	~1218
START SECTOR # OF DRIVE/ PARTITION	~1220
PHYSICAL DRIVE CHARACTERISTICS	~1202

1200

FIG. 12